

PRODUCT SPEC SHEET

Model No	20A0155-A01-E001	
Product Name	Main Controller	
Spec		
Feature	Output communication protocol	TTL
	Drive capability	512 points @24fps each channel
	Memory	SD Card
	Supported LED models	WS2811,WS2812,SK6812,SK6822,AP102,AP103,W S2815
	DC INPUT	DC12V 10A Max
	DC OUTPUT	DC12V 2A Max
I/O Ports	DC IN	*3(DC5.5*2.5mm)
	DC OUT	*4(DC5.5*2.5mm)
	LED Port	*2(5569-2*3P) for 12V full color LED *2(5569-2*2P) for 5V full color LED
	USB C Port	*1(Standard Type C)
	USB A Port	*1(Standard USB A) for DC5V output
	Sensor IN	*1(5569-2P) for sensor input
	SD	*1 (Standard SD slot)
	Accessories	Adapter
Power cable		Non
USB cable		Non
HDMI cable		Non
User manual		Non
Warranty card		Non
Environment	Remote control	Non
	Operating Temperature	0°C to 40°C
	Storage Temperature	-10°C to 60°C
	Humidity	20%-75% RH at 40°C
Certification		FCC, CE
Product Size	L*W*H	350.1*77.3*26.3

Product图示:

